




Bourdon tube pressure gauges for industrial applications RF100I

Part no. 85304211

Bourdon tube pressure gauges for industrial applications Type D2

benefits

- for machine and plant engineering
- robust steel housing
- many customised versions available

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys.

! For high measuring accuracy. For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type

D2

Nominal size

100

accuracy class (EN 837-1/6)

1.0

ranges (EN 837-1/5)

see ordering table

application area

≤ 600 bar: Full scale value
 > 600 bar: $\frac{3}{4}$ x full scale value
 ≤ 600 bar: 0.9 x full scale value
 > 600 bar: $\frac{2}{3}$ x full scale value
 ≤ 600 bar: 1.3 x full scale value
 > 600 bar: Full scale value

Operating temperature range

Medium: max. 60°C

Ambient: $-20/+60^{\circ}\text{C}$

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20°C :

at rising temperature approx. $\pm 0.4\%$ /10 K

falling temperature approx. $\pm 0.4\%$ /10 K

of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Brass, bottom back

Measuring element

Bourdon tube

≤ 60 bar: "C" type tube, Copper alloy

> 60 bar: helical tube, stainless steel 316 Ti/316 L

movement
Brass

Dial
Aluminium, white
Scaling: black

Pointer
Aluminium, black


Options

- throttle screw
- Reference pointer
- Electrical contacts
- special scales
- other process connections

Housing
Sheet steel, black

window
Plastic, clipped in

Technical Drawings



Versions

Range	Mounting type	Type	Part number
-1/+3 bar	direct	RF100I D211	85304211

- ☒ in-stock items
- ☐ Non-stock items