



Bourdon tube pressure gauge RF50 rad

Part no. 63124

Bourdon tube pressure gauge RF for heating/plumbing

benefits

- with self-sealing connection thread (NG 50 and 63) for fast mounting
- corrosion-resistant housing

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys and EPDM.
! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Nominal size

50

accuracy class (EN 837-1/6)

2.5

ranges

0/16 bar

application area

static load: $\frac{3}{4}$ x full scale value
dynamic load: $\frac{2}{3}$ x full scale value
short-term: Full scale value

Operating temperature range

Medium: max. 60 °C
Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. ± 0.4 %/10 K
falling temperature approx. ± 0.4 %/10 K
of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Brass, bottom
NG 50
G $\frac{1}{4}$ B, Self-sealing with PTFE sealing ring

Measuring element

Bourdon tube, "C" type tube
Copper alloy

movement

Brass

<p>Dial Plastic, white Scaling: black</p> <p>Pointer Plastic, black</p>	<p>Housing Plastic (ABS), black, highly impact-resistant and corrosion-resistant</p> <p>window Plastic, clipped in NG 50</p>
---	--

Versions

	housing ø	Connec- tion	Connec- tion	Thread	alignment	Range	Type		Part no.
RF50	50 mm	G½B		Self-sea- ling with PTFE sealing ring	bottom	0/16 bar	RF50 rad	●	63124

- in-stock items
- Non-stock items