



Heating pump assembly PrimoTherm® K 180-1 DN32 WP

Part no. 79504

Heating pump assembly

benefits

- pre-assembled, tightness-tested and heat-insulated assembly
- compact design
- available with high energy efficiency pump class A
- easy, fast mounting



Application

Heating pump assembly for use in non-mixed heating circuits, specially for storage tank charging. It connects the heating boiler and the pipe system.

Description

Complete, pre-assembled and tightness-tested heating pump assembly with all required functional components, form-fit insulation and wall mounting unit. System connection: Primary end (consumer) G1¼ female

The pump line (flow/hot) consists of:

Combination valve with thermometer in the hand wheel (red mark, range 0/120 °C)

Ball valve below the pump, suitable for use of pumps with 2" x 180 mm

System connection G1¼ female (heating circuit)

The return line consists of:

Combination valve with thermometer in the hand wheel (blue mark, range 0/120 °C)

Pipe for length compensation with gravity brake

System connection (boiler) G2 with screw connection G1¼ female (easy mounting and adapter G1½ AB for use with boiler manifold)

Technical Specifications

Axis distance

125 mm

system connections

Boiler: G1¼ IG

Heating circuit: G1¼ IG

Operating temperature range

Medium: max. 110 °C

System pressure

max. 10 bar

observe maximum pressure of circulation pumps used

Nominal size

DN 32

Flow coefficient Kvs
21 m³/h

Heat insulation
Polypropylene EPP

Dimensions
W x H x D: 248 x 480 x 170 mm

Circulation pump
Wilo Para OPT 30-180/8-60/SC

Supply voltage
AC 230 V, 50 Hz

Power input
Wilo Para OPT 30-180/8-60/SC

pumping head
Wilo Para OPT 30-180/8-60/SC

pumping volume
Wilo Para OPT 30-180/8-60/SC


operating modes/settings
Wilo Para OPT 30-180/8-60/SC

Options
• with high-efficiency pump EEI 0,2

Options

- with high-efficiency pump EEI 0,2

Technical Drawings



Versions

	opening temperature is reached	Pump		Part no.
Heating pump assembly PrimoTherm® K 180-1 DN32 WP		Wilo Para OPT 30-180/8-60/SC	●	79504

- in-stock items
- Non-stock items