

PRODUCT DATA SHEET

EVERBUILD® Creocote

OIL BASED EXTERIOR TIMBER TREATMENT

PRODUCT DESCRIPTION

EVERBUILD® Creocote is an oil based wood treatment, effective when applied to exterior timbers such as garden sheds, fences and trellis work. The oil based properties provide excellent surface water repellence and restricts weather damage. The product improves grain definition and exhibits the characteristic odour familiar to traditional Creosote users.

USES

For treating exterior timbers such as garden sheds, fences and trellis work.

CHARACTERISTICS / ADVANTAGES

- Oil based, excellent water repellency
- Improves grain definition
- Ideal for use on external timbers

PRODUCT INFORMATION

Packaging	4ltr and 20ltr jerry cans
Appearance / Colour	Light Brown and Dark Brown
Shelf Life	Use within 12 months.
Storage Conditions	Store at 5 - 25°C in original containers away from children

APPLICATION INFORMATION

Consumption	Depending upon the texture and porosity of the timber to be treated, application of a single coat of EVERBUILD® Creocote will cover at the rate of 1 litre per 6 to 8 square meters.
--------------------	--

APPLICATION INSTRUCTIONS

EVERBUILD® Creocote can be applied by brush, spray or dip methods. Ensure that all timbers are structurally sound, dry and free from surface growths. Care should be taken to protect valuable plants and foliage during application. Timber previously treated with Creosote, Creosote Substitute or a solvent based wood preservative will readily accept re-treatment with EVERBUILD® Creocote. Sealed or painted timbers must be stripped back to bare wood before coating with this product. To ensure suitability it is recommended that test patches are applied before general application. Apply liberally, soaking the timber to achieve best res-

ults. Always ensure that end-grain timbers are fully saturated. For timbers being set in the ground, apply Everbuild Bitumen Paints to protect against groundwater saturation. Children and pets should be kept away from treated timber until they are completely dry. A deeper colour may be attained by applying further treatments.

LIMITATIONS

- Ready to use - do not dilute.
- For External use only.
- Do not use on painted or sealed wooden surfaces.
- It is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services De-

partment for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDCreocote-en-GBEVER-(04-2018)-1-1.pdf

Product Data Sheet
EVERBUILD® Creocote
April 2018, Version 01.01
021405061000000038