

Sika Damp-proofing Slurry

DECLARATION OF PERFORMANCE No. 40353112

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	SKDPSLUR
2	INTENDED USE/S	Waterproofing / damp-proofing cementitious slurry for use as a surface protection system Principles 1.3, 2.2 & 8.2
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW, UK
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	2+
6a	HARMONISED STANDARD:	EN1504-2:2004
	Notified body/ies:	1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Permeability to CO2	SD >50 m		EN1504-2:2004
Water vapour permeability	Class 1		
Capillary absorption and permeability to water	w ≤ 0.1 kg/m ² .hr 0.5		
Thermal compatibility	NPD		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Crack bridging ability	NPD		
Adhesion strength by pull off	≥1 N/mm ²		
Reaction to fire	F		
Release of dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 15 December 2020

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 16 December 2020



End of information as required by Regulation (EU) No 305/2011



Everbuild Building Products LTD, Leeds, UK

DoP No. 40353112

EN1504-2:2004

Notified Body 1029

Waterproofing / damp-proofing cementitious slurry for use as a surface protection system

Principles 1.3, 2.2 & 8.2

Permeability to CO ₂	SD >50 m
Water vapour permeability	Class 1
Capillary absorption and permeability to water	w ≤ 0.1 kg/m ² .hr 0.5
Thermal compatibility	NPD
Resistance to thermal shock	NPD
Chemical resistance	NPD
Crack bridging ability	NPD
Adhesion strength by pull off	≥1 N/mm ²
Reaction to fire	F
Release of dangerous substances	NPD

www.everbuild.co.uk/downloads/

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SKDPSLUR

40353112

2020/12, ver. 02

1213

3/4

Template for translation. Only for
internal use

BUILDING TRUST



