
Everbuild® 201 Mortar Admix

DECLARATION OF PERFORMANCE

No. 93462845

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	ADM
2	INTENDED USE/S	Air entraining/plasticizing mixture
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	2+
6a	HARMONISED STANDARD:	BS EN 934-3:2009 +A1:2012
	Notified body/ies:	0120

Declaration of Performance

ADM
93462845
2021/06 , ver. 01
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Dangerous substances	See sds		
Chloride ion content	<0.1 % w/w		
Alkali content	<1 % w/w		
Corrosion behaviour	Contains only components from EN934-1:2008 annex A1		
Compressive strength	Test mix > 70 % of control		BS EN 934-3: 2009
Entrained air			+A1:2012
Initial	14-20 %		
After 1 hour standing	≥initial –3 %		
After extended mixing	Initial ± 5 %		
Reduction in water requirement	≥ 8 % by mass		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 11 June 2021

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 11 June 2021


.....

End of information as required by UKCA

Declaration of Performance

ADM
93462845
2021/06 , ver. 05
1213



21

Everbuild Building Products LTD, Leeds, UK

DoP No. 93462845

BS EN 934-3:2009 + A1: 2012

Notified Body 0120

Air entraining / plasticizing mixture

Dangerous substances	See sds
Chloride ion content	<0.1 % w/w
Alkali content	<1 % w/w
Corrosion behaviour	Contains only components from EN934-1:2008 annex A1
Compressive strength	Test mix > 70 % of control
Entrained air	
Initial	14-20 %
After 1 hour standing	≥initial –3 %
After extended mixing	Initial ± 5 %
Reduction in water requirement	≥ 8 % by mass

[For DOC see www.everbuild.co.uk](http://www.everbuild.co.uk)

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

ADM

93462845

2021/06, ver. 05

1213

3/4

BUILDING TRUST



Declaration of Performance

ADM

93462845

2021/06 , ver. 05

1213

4/4

BUILDING TRUST

